

## Dielectrically impeded discharge lamp having a spacer

5

## Technical Field

The invention proceeds from a discharge lamp in accordance with the preamble of Claim 1.

10

Here, the term "discharge lamp" covers sources of electromagnetic radiation based on gas discharges. The spectrum of the radiation can in this case comprise both the visible region and the UV (ultraviolet)/VUV (vacuum ultraviolet) region as well as the IR (infrared) region. Furthermore, it is also possible to provide a fluorescent layer for converting invisible into visible radiation.

15

20 Discharge lamps having so-called dielectrically impeded electrodes are also concerned. Here, the dielectrically impeded electrodes are typically implemented in the form of thin metallic strips which are arranged on the outer and/or inner wall of the discharge vessel. If all  
25 the electrodes are arranged on the inner wall, at least some of these electrodes must be completely covered from the interior of the discharge vessel by a dielectric layer. Discharge lamps of this type are usually denoted as dielectrically impeded discharge  
30 lamps or dielectric barrier discharge lamps, sometimes also as silent discharge lamps, and are disclosed, for example, in EP 0 363 832 (Figure 3) and WO 98/43279 (Figures 3a, 3b).

35 More precisely, the invention relates to the abovenamed type of lamp having a large-area discharge vessel, in particular so-called flat lamps. Such lamps typically have two, at least partially and approximately plane,

discharge vessel walls which are adjacent to one another in parallel.

5 These two vessel walls, referred to below for shortness  
as front plate and baseplate respectively, are usually  
connected to one another in a gas-tight fashion via a  
frame, and thereby form the discharge vessel.  
Alternatively, the baseplate and/or front plate can be  
shaped such that a discharge vessel is formed as soon  
10 as they are joined. For example, the baseplate and/or  
front plate can be shaped like a trough, for example by  
deep drawing of a plane glass plate. In the case of  
flat lamps of very large area, the predominant fraction  
of the shaped baseplate or front plate is at least  
15 approximately plane in this case as well. In this case  
such a lamp requires, for stabilization purposes, one  
or more support points, also denoted as spacers below.

20 This holds all the more so since a discharge lamp  
contains a gas filling of defined composition and  
filling pressure, and must therefore be evacuated  
before the filling. Consequently, the discharge vessel  
must permanently resist both underpressure -  
specifically during the production of the lamp - and  
25 the later filling pressure which, in the case of such a  
lamp, is usually less than atmospheric pressure, for  
example between 10 kPa and 20 kPa. This is achieved by  
means of the said spacers, which are arranged between  
the baseplate and front plate of the discharge vessel  
30 in sufficient numbers and in a suitable position. Each  
spacer rests in this case on two mutually opposite  
bearing surfaces of the two plates, and thus supports  
the latter against one another. The positioning of the  
spacers must be performed in such a way that the  
35 discharge, which burns in the form of numerous partial  
discharges in a fashion essentially parallel to the  
baseplate of the plane discharge vessel, is not  
influenced, or is influenced only slightly at most. For  
this reason, and in order to impair as little as

09710985-034504  
F05520-98007200

possible the luminance on the front plate of the plane  
discharge vessel, the extent of the bearing surface of  
each spacer is kept as small as possible, in any case  
to the extent ensuring a reliable support function of  
5 the spacers.

#### Prior Art

Document EP 0 324 953 A1 discloses a flat radiator  
10 having dielectrically impeded electrodes and spacers  
(for example Figure 1). The spacers are formed by  
elongated distance pieces made from insulating  
material.

15 Also known, moreover, are spacers of different shapes,  
for example in the form of columns or spheres.  
Different cross-sectional shapes are conceivable in the  
case of a column. In any case, the individual spacers  
are usually brought to the desired dimensions by  
20 grinding and polishing. It is disadvantageous in this  
case that these spacers are reflected as relatively  
dark spots in the luminous front plate of the lamp.

#### Summary of the Invention

25 It is the object of the present invention to provide a  
discharge lamp in accordance with the preamble of Claim  
1, in which the spacers are visible as little as  
possible.

30 This object is achieved by means of the characterising  
features of Claim 1. Particularly advantageous  
embodiments are to be found in the dependent claims.

35 According to the invention, the or each spacer is  
provided with an optically diffuse surface at least in  
the region of one bearing surface. Alternatively, the  
entire surface of the or each spacer can also be  
provided with a diffuse surface.

00749986-011504  
FOSTER 5567200

The diffuse surface can be implemented by frosting, for example by etching using hydrofluoric acid, by sand blasting or the like. Or alternatively, the diffuse  
5 surface can also be implemented by a thin frosted-white coloured layer.

It is advantageous, in addition, when the area of the bearing surface is as small as possible so that the  
10 latter can be detected as little as possible by comparison with the extent of the front plate. However, the bearing surface should not be minimised in such a way that it is to be regarded as being quasi-puntiform in the extreme case, since this could increase  
15 impermissibly local loading of the discharge vessel plates. Rather, the bearing surfaces which have proved themselves are those which support a relatively large surface despite a small area, for example cruciform bearing surfaces. The arms of the cross are preferably  
20 of relatively narrow design by comparison with a rectangle, which can be regarded as defined by the cross.

A particular problem is added when the or each spacer  
25 is formed by a body which has a thickened portion between the two bearing surfaces, for example a polished sphere. Specifically, it has proved that in this case, during operation of the lamp, each bearing surface is imaged as a dark "point" on the front plate  
30 of the lamp. A dark aureole appears around this "point". The cause of this seems to be the casting of the shadow of the sphere against the inner wall of the front plate.

35 According to the invention, at least the bearing surface of the sphere is frosted. Moreover, the upper hemisphere of the sphere, that is to say that hemisphere whose pole lies inside the bearing surface of the sphere with the inner wall of the front plate,

FOOTED 09400

is additionally coated with fluorescent material. However, the bearing surface itself is excluded from the fluorescent material, or the fluorescent layer is at least thinner on the bearing surface. Evidently, the  
5 fluorescent layer on the "upper" hemisphere of the sphere reflects or scatters light into the region shaded by the sphere, thus avoiding the abovenamed dark aureole. The uncoated "lower" hemisphere, by contrast, allows the sphere to be entered by light which partly  
10 passes out of the bearing surface and through the front plate, thus preventing the production of the abovenamed dark "point" on the front plate.

In a development, the surface of the or each spacer is  
15 treated in such a way that the or each relevant surface, possibly with the exception of the bearing surface, has the properties of a "radiation trap". What is meant by this is that the optical properties of the respective surface are specifically varied in such a  
20 way that the light beams impinging on this surface are preferably refracted into the relevant spacer and in so doing contribute to lighting this spacer.

This can be achieved, for example, by a multiplicity of  
25 suitable microstructures, in particular in the form of prisms or pyramids, on the surface of the or each spacer. The effect of the radiation trap is based in this case on the fact that some of the light beams reflected by a structure impinge on an immediately  
30 adjacent structure and are refracted at least partially by this structure into the relevant spacer.

Alternatively, the effect of the radiation trap can also be achieved by a type of anti-reflection  
35 interference layer which is applied to the surface of the or each spacer. However, this variant is technically complicated, since interference layers are typically implemented by a stack of thin layers of alternately high or low refractive index.

The material of the spacers consists in each case of optically transparent material, for example glass. Only then are the light beams injected into the spacers capable of passing through the latter at all, that is to say of re-emerging from the spacers without unacceptably high losses, and thereby contributing to lighting it up. As a result, the spacers on the front plate can be detected as little as possible, that is to say the homogeneity of the luminance distribution on the front plate is impaired as little as possible.

Protection is also claimed for such a spacer whose surface is at least partially optically diffuse.

#### Description of the Drawings

The invention is to be explained in more detail below with the aid of a plurality of exemplary embodiments. In the drawings:

Figure 1 shows the arrangement of spacers in a typical electrode configuration of a flat radiator lamp,

Figure 2 shows a spacer in a detailed and cross-sectional illustration from Figure 1,

Figure 3a shows a further exemplary embodiment of a spacer, in top view, and

Figure 3b shows the spacer from Figure 3a in a side view.

Figure 1 shows a schematic illustration of the arrangement of spacers 1 in a typical electrode configuration of a flat radiator lamp for background lighting of a liquid crystal display screen (not illustrated), in relation to which further reference is made to document WO 98/43276. Elongated anodes 3 and cathodes 4 are arranged alternately on the baseplate 2. The cathodes 4 have nose-like projections 5 (cf. WO 98/11596), at which a partial discharge forms in

5

15

20

30

A prismatic foil 11 (brightness enhancement foil from the 3M), is situated on the outside of the front plate

A reflection layer 12 is also located on the baseplate 5 2 below the fluorescent layer 10.

10

15

20

25